

HEAVY-WALL HEAT SHRINK TUBING WITH ADHESIVE



Technical description

Color: Black Material: Polyolefin Excellent electrical and environmental insulation Excellent impact and abrasion resistance Ideal for low voltage applications UV resistant All dimensions are in mm



| Code | As supplied: inside Ø | After recovery: inside diameter (max.) | After recovery: wall thick. | Bars length mt |
|-----------|-----------------------|--|-----------------------------|----------------|
| 14333RA01 | 16,0 | 4,0 | 2,40 | 1,22 |
| 14334RA01 | 24,0 | 6,0 | 2,6 | 1,22 |
| 14335RA01 | 34,0 | 8,0 | 3,2 | 1,22 |
| 14336RA01 | 48,0 | 12,0 | 4,0 | 1,22 |
| 14337RA01 | 55,0 | 16,0 | 4,0 | 1,22 |
| 14338RA01 | 75,0 | 22,0 | 4,0 | 1,22 |
| 14339RA01 | 95,0 | 25,0 | 4,0 | 1,22 |
| 14340RA01 | 130,0 | 35,0 | 4,2 | 1,22 |

| Code | As supplied: inside Ø | After recovery: inside diameter (max.) | After recovery: wall thick. | Bars length mt |
|-----------|-----------------------|--|-----------------------------|----------------|
| 14342RA01 | 160,0 | 50,0 | 4,2 | 1,22 |
| 14343RA01 | 180,0 | 50,0 | 4,2 | 1,22 |
| 14344RA01 | 200,0 | 60,0 | 4,2 | 1,22 |
| 14345RA01 | 235,0 | 65,0 | 4,4 | 1,22 |
| 14346RA01 | 265,0 | 75,0 | 4,8 | 1,22 |
| 15983RA01 | 12,0 | 3,0 | 2,0 | 1,22 |