

METRIC THREAD IP 65 SCREW PLUG



RAL 7001



RAL 7035



Technical description

Material: PA

Working temperature: -30°C ~ +100° C


UL Flammability : HB (UL94)

Colour: See table

Metric as per EN 60423

Protection grade = IP65

All dimensions are in mm.



Code	A	B	C	D	Colour	MOQ-Pcs
8881AA019005	M12x1,5	6,0	10,0	15,0	RAL 9005	100
8881AA117001	M12x1,5	6,0	10,0	15,0	RAL 7001	100
8881AA117035	M12x1,5	6,0	10,0	15,0	RAL 7035	100
8882AA019005	M16x1,5	6,0	10,5	20,0	RAL 9005	100
8882AA117001	M16x1,5	6,0	10,5	20,0	RAL 7001	100
8882AA117035	M16x1,5	6,0	10,5	20,0	RAL 7035	100
8883AA019005	M20x1,5	6,0	10,5	24,0	RAL 9005	100
8883AA117001	M20x1,5	6,0	10,5	24,0	RAL 7001	100
8883AA117035	M20x1,5	6,0	10,5	24,0	RAL 7035	100
8884AA019005	M25x1,5	8,0	13,0	30,0	RAL 9005	100
8884AA117001	M25x1,5	8,0	13,0	30,0	RAL 7001	100
8884AA117035	M25x1,5	8,0	13,0	30,0	RAL 7035	100
8885AA019005	M32x1,5	8,0	13,5	37,0	RAL 9005	100
8885AA117001	M32x1,5	8,0	13,5	37,0	RAL 7001	100
8885AA117035	M32x1,5	8,0	13,5	37,0	RAL 7035	100
8886AA019005	M40x1,5	8,0	14,0	46,0	RAL 9005	50
8886AA117001	M40x1,5	8,0	14,0	46,0	RAL 7001	50

Code	A	B	C	D	Colour	MOQ-Pcs
8886AA117035	M40x1,5	8,0	14,0	46,0	RAL 7035	50
8887AA019005	M50x1,5	10,0	16,5	56,0	RAL 9005	50
8887AA117001	M50x1,5	10,0	16,5	56,0	RAL 7001	50
8887AA117035	M50x1,5	10,0	16,5	56,0	RAL 7035	50
8888AA019005	M63x1,5	12,0	17,0	70,0	RAL 9005	50
8888AA117001	M63x1,5	12,0	17,0	70,0	RAL 7001	50
8888AA117035	M63x1,5	12,0	17,0	70,0	RAL 7035	50