

PRINT MULTI HOLE SNAP FIT IP 67 GROMMET



Technical description

Material: TPE

Colours: Grey Ral 7035 (white & black on special request)


Degree of protection = IP67

Panel: see Table

Working temperature: -50°C ~ +125° C

All dimensions are in mm

*The fee may vary depending on the thickness of the material on which it is installed.



Code	A	B	C	D	E	Size	Mounting hole	Thickness	Colour	Ø cable diameter	MOQ-Pcs
9051PF019005	27,5	3,0	11,0	4,0	6,7	M20	20,5	0,5 - 3	Nero RAL 9005	3X 4 - 7	500
9051PF029010	27,5	3,0	11,0	4,0	6,7	M20	20,5	0,5 - 3	Bianco RAL 9010	3X 4 - 7	500
9051PF117035	27,5	3,0	11,0	4,0	6,7	M20	20,5	0,5 - 3	Grigio RAL 7035	3X 4 - 7	500
9052PF019005	32,5	3,0	11,0	4,0	6,7	M25	25,5	0,5 - 3,5	Nero RAL 9005	3X 4 - 9	500
9052PF029010	32,5	3,0	11,0	4,0	6,7	M25	25,5	0,5 - 3,5	Bianco RAL 9010	3X 4 - 9	500
9052PF117035	32,5	3,0	11,0	4,0	6,7	M25	25,5	0,5 - 3,5	Grigio RAL 7035	3X 4 - 9	500
9053PF019005	26,0	3,0	11,0	4,0	6,7	PG11/18,6	19,0	0,5 - 3	Nero RAL 9005	3X 4 - 6	500
9053PF029010	26,0	3,0	11,0	4,0	6,7	PG11/18,6	19,0	0,5 - 3	Bianco RAL 9010	3X 4 - 6	500
9053PF117035	26,0	3,0	11,0	4,0	6,7	PG11/18,6	19,0	0,5 - 3	Grigio RAL 7035	3X 4 - 6	500
9054PF019005	30,0	3,0	11,0	4,0	6,7	PG16/22,5	23,0	0,5 - 3,5	Nero RAL 9005	3X 4 - 8	500
9054PF029010	30,0	3,0	11,0	4,0	6,7	PG16/22,5	23,0	0,5 - 3,5	Bianco RAL 9010	3X 4 - 8	500
9054PF117035	30,0	3,0	11,0	4,0	6,7	PG16/22,5	23,0	0,5 - 3,5	Grigio RAL 7035	3X 4 - 8	500