

THIN-WALL HEAT SHRINK TUBING 2:1 / 125°C



Technical description



Code	Before recovery: inside diameter	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	PKG.MT
14221RA01	1,2	0,6	0,33	150
14222RA01	1,6	0,8	0,36	150
14223RA01	2,4	1,2	0,42	150
14224RA01	3,2	1,6	0,42	150
14225RA01	4,8	2,4	0,52	75
14226RA01	6,4	3,2	0,54	75
14227RA01	9,5	4,8	0,54	75
14228RA01	12,7	6,4	0,62	50
14229RA01	16,0	8,0	0,67	50
14230RA01	19,0	9,5	0,75	30
14231RA01	25,4	12,7	0,85	30
14232RA01	31,8	15,9	0,85	30
14233RA01	38,1	19,1	0,96	30
14234RA01	50,8	25,4	0,97	30

Code	Before recovery: inside diameter	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	PKG.MT
14235RA01	76,2	38,1	1,17	15
14236RA01	101,6	50,8	1,30	15
14237RA01	127,0	63,5	1,30	15
14238RA01	152,4	76,2	1,30	15