

SEPARADORES DE CIRCUITO IMPRESO Ø 4,0 / Ø 5.0



Descripción Técnica


Material: PA66

Color: Negro

Autoextinguibilidad: UL94-HB

Temperatura de trabajo: -35°C ~ +130°C

Todas las medidas están indicadas en mm



Codigo	A	B	C	D	Orificio Superior	Espesor superior	Orificio Inferior	Espesor inferior	Conf./piezas
10004AA0104.0	9,0	1,7	4,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0105.0	9,0	1,7	5,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0106.0	9,0	1,7	6,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0107.0	9,0	1,7	7,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0108.0	9,0	1,7	8,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500

Codigo	A	B	C	D	Orificio Superior	Espesor superior	Orificio Inferior	Espesor inferior	Conf./piezas
10004AA0109.0	9,0	1,7	9,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0110.0	9,0	1,7	10,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0111.0	9,0	1,7	11,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0112.0	9,0	1,7	12,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0113.0	9,0	1,7	13,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0114.0	9,0	1,7	14,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0115.0	9,0	1,7	15,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0116.0	9,0	1,7	16,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0117.0	9,0	1,7	17,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0118.0	9,0	1,7	18,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0119.0	9,0	1,7	19,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0120.0	9,0	1,7	20,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0121.0	9,0	1,7	21,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0122.0	9,0	1,7	22,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0123.0	9,0	1,7	23,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0124.0	9,0	1,7	24,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0125.0	9,0	1,7	25,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0126.0	9,0	1,7	26,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0127.0	9,0	1,7	27,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0128.0	9,0	1,7	28,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0129.0	9,0	1,7	29,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0130.0	9,0	1,7	30,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0131.0	9,0	1,7	31,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0132.0	9,0	1,7	32,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0133.0	9,0	1,7	33,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0134.0	9,0	1,7	34,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0135.0	9,0	1,7	35,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500
10004AA0136.0	9,0	1,7	36,0	9,8	Ø 3,2	1,5	Ø 5,0	3,0	500