

DISTANZIATORI METRICI M3 FILETTATI CON AGGANCIO Ø 4,0



Descrizione tecnica

Materiale: PA 6.6


Colore: nero

Autoestinguenza: HB (UL 94)


Temperatura esercizio: -35°C ~ +130°C

Altre altezze su richiesta speciale

Tutte le quote sono in mm









Codice	Α	В	С	D	Foro	Spessore	Conf./pezzi
5939AA0105.0	5,0	М3	3,0	6,0	Ø 4,0	1,8	1.000
5939AA0106.0	6,0	М3	4,0	6,0	Ø 4,0	1,8	1.000
5939AA0107.0	7,0	М3	5,0	6,0	Ø 4,0	1,8	1.000
5939AA0108.0	8,0	М3	6,0	6,0	Ø 4,0	1,8	1.000
5939AA0109.0	9,0	МЗ	7,0	6,0	Ø 4,0	1,8	1.000
5939AA0110.0	10,0	М3	8,0	6,0	Ø 4,0	1,8	1.000
5939AA0111.0	11,0	МЗ	9,0	6,0	Ø 4,0	1,8	1.000
5939AA0112.0	12,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0113.0	13,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0114.0	14,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0115.0	15,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0116.0	16,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0117.0	17,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0118.0	18,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0119.0	19,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0120.0	20,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0121.0	21,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0122.0	22,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0123.0	23,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0124.0	24,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0125.0	25,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0126.0	26,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0127.0	27,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0128.0	28,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0129.0	29,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0130.0	30,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0131.0	31,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0132.0	32,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0133.0	33,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0134.0	34,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0135.0	35,0	М3	10,0	6,0	Ø 4,0	1,8	1.000



Codice	Α	В	С	D	Foro	Spessore	Conf./pezzi
5939AA0136.0	36,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0137.0	37,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0138.0	38,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0139.0	39,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0140.0	40,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0141.0	41,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0142.0	42,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0143.0	43,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0144.0	44,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0145.0	45,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0146.0	46,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0147.0	47,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0148.0	48,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0149.0	49,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0150.0	50,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0151.0	51,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0152.0	52,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0153.0	53,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0154.0	54,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0155.0	55,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0156.0	56,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0157.0	57,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0158.0	58,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0159.0	59,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0160.0	60,0	М3	10,0	6,0	Ø 4,0	1,8	1.000
5939AA0161.0	61,0	М3	10,0	6,0	Ø 4,0	1,8	1.000