

DISTANZIATORI METRICI M4 CON AGGANCIO RAPIDO Ø 3,8



Descrizione tecnica


Materiale: PA 6.6

Colore: nero

Autoestinguenza: HB (UL 94)

Temperatura esercizio: -30°C ~ +150°C

Tutte le quote sono in mm



Codice	A	B	C	D	E	Foro	Spessore	Conf./pezzi
8208AA0103.0	3,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0104.0	4,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0105.0	5,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0106.0	6,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0107.0	7,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0108.0	8,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0109.0	9,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0110.0	10,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0111.0	11,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0112.0	12,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0113.0	13,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0114.0	14,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0115.0	15,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0116.0	16,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0117.0	17,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0118.0	18,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0119.0	19,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0120.0	20,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0121.0	21,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0122.0	22,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0123.0	23,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0124.0	24,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0125.0	25,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0126.0	26,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0127.0	27,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0128.0	28,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0129.0	29,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0130.0	30,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0131.0	31,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0132.0	32,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0133.0	33,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500

Codice	A	B	C	D	E	Foro	Spessore	Conf./pezzi
8208AA0134.0	34,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0135.0	35,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0136.0	36,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0137.0	37,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0138.0	38,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0139.0	39,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0140.0	40,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0141.0	41,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0142.0	42,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0143.0	43,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0144.0	44,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0145.0	45,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0146.0	46,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0147.0	47,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0148.0	48,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0149.0	49,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0150.0	50,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0151.0	51,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0152.0	52,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0153.0	53,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0154.0	54,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0155.0	55,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0156.0	56,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0157.0	57,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0158.0	58,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0159.0	59,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0160.0	60,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0161.0	61,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0162.0	62,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0163.0	63,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500
8208AA0164.0	64,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500

Codice	A	B	C	D	E	Foro	Spessore	Conf./pezzi
8208AA0165.0	65,0	6,0	M4	8,0	4,7	Ø 3,8	1,8	500