


REVISIONS			
REV	DESCRIPTION	DATE	BY



**Colour: Black**  
**Material: Crosslinked co-extruded adhesive lined Polyolefin**  
**Shrink ratio: 3:1**  
**Flammability: UL224 VW-1**  
**Flame retardant**  
**Excellent sealing and insulation properties**  
**UV resistant**  
**Operating temperature: -55 °C +125 °C**  
**Minimum shrink temperature: +70 °C**  
**Minimum full recovery temperature: +110 °C**  
**Longitudinal change 0 ± 10% max.**  
**All dimensions are in mm**

P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)
14826RA01	3,0	1,0	1,00
14827RA01	4,8	1,5	1,00
14828RA01	6,0	2,0	1,00
14829RA01	9,0	3,0	1,35
14830RA01	12,0	4,0	1,65
14831RA01	19,0	6,4	2,10
14832RA01	24,0	8,0	2,35
14833RA01	30,0	10,0	2,40
14834RA01	40,0	13,0	2,40

				TITLE <b>DUAL-WALL HEAT SHRINK TUBING 3:1 ADHESIVE LINED</b>	
				MATERIAL SEE ABOVE	
PART NUMBER SEE TABLE				DRAWING NUMBER 21.06.08.XXXX.0.E	
				COLOR SEE ABOVE	
SIZE A4	SCALE NTS	UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
				APPROVED	