



P/N	A	B	C	Hole	Thickness
9909EA01	14,2	13,5	5,5	Ø 3,1	0,8 - 1,8
9910EA01	14,2	13,5	5,5	Ø 3,1	1,8 - 2,8
9788EA01	21,0	20,0	4,2	Ø 4,1	0,8 - 1,8
9789EA01	21,0	20,0	4,2	Ø 4,1	1,8 - 2,8
9790EA01	21,0	20,0	4,2	Ø 4,1	2,9 - 3,7
9791EA01	21,0	20,0	4,2	Ø 4,1	3,8 - 4,8
9792EA01	15,0	14,0	6,0	Ø 4,1	0,6 - 1,0
9793EA01	15,0	14,0	6,0	Ø 4,1	1,0 - 2,0
9794EA01	15,0	14,0	6,0	Ø 4,1	2,0 - 3,1
9795EA01	15,0	14,0	6,0	Ø 5,1	0,8 - 1,2
9796EA01	15,0	14,0	6,0	Ø 5,1	1,3 - 2,3
9797EA01	21,0	20,0	6,0	Ø 4,1	0,8 - 1,8
9798EA01	21,0	20,0	6,0	Ø 4,1	1,9 - 2,8
9799EA01	21,0	20,0	6,0	Ø 4,1	2,9 - 4,0
9800EA01	21,0	20,0	8,0	Ø 4,1	≤ 0,8
9801EA01	21,0	20,0	8,0	Ø 4,1	0,8 - 2,0
9802EA01	21,0	20,0	8,0	Ø 4,1	2,1 - 3,1
9911EA01	15,0	14,0	9,0	Ø 4,1	0,6 - 1,0
9803EA01	15,0	14,0	9,0	Ø 4,1	1,0 - 2,0
9804EA01	15,0	14,0	9,0	Ø 4,1	2,0 - 3,1
9912EA01	15,0	14,0	9,0	Ø 5,1	0,8 - 1,2
9913EA01	15,0	14,0	9,0	Ø 5,1	1,3 - 2,3
9805EA01	10,8	10,0	4,0	Ø 3,6	0,5 - 1,2
9806EA01	10,8	10,0	4,0	Ø 3,6	1,0 - 2,0
9807EA01	10,8	10,0	4,0	Ø 3,6	1,5 - 2,5
9808EA01	10,8	10,0	4,0	Ø 3,6	2,5 - 3,5
9809EA01	10,8	10,0	4,0	Ø 3,6	3,5 - 4,5

REVISIONS			
REV	DESCRIPTION	DATE	BY

BEFORE INSERTION



AFTER INSERTION



NOTES:
BODY MATERIAL: TPE
PIN MATERIAL: PA 6
COLOUR: BLACK
FLAMMABILITY:
-TPE: HB (UL94)
- PA 6: V2 (UL94)
WORKING TEMPERATURE: -35°C ~ +90°C

	DESCRIPTION		TITLE: FEETS WITH SNAP RIVET		DWG UNIT: MM
	MATERIAL: SEE ABOVE		Modelled in RHINO 4.0	FILE:	DwN: 11/05/21
	COLOUR: SEE ABOVE		TOLLERANCES UNLESS NOTED	SHEET: 1 OF 1	ChkD: DT:21.05.11.XXXXX.0.E
			SEE ABOVE	SCALE: NTS	Part Number: SEE TABLE
REV.		DATE			

