



REVISIONS			
REV	DESCRIPTION	DATE	BY




P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Reel / Meter
14277RA01	1,2	0,6	0,33	300
14278RA01	1,6	0,8	0,36	300
14279RA01	2,4	1,2	0,42	300
14280RA01	3,2	1,6	0,42	300
14281RA01	4,8	2,4	0,51	150
14282RA01	6,4	3,2	0,54	150
14283RA01	9,5	4,8	0,54	75
14284RA01	12,7	6,4	0,62	75
14285RA01	16,0	8,0	0,69	75
14286RA01	19,0	9,5	0,75	50
14287RA01	25,4	12,7	0,85	50
14288RA01	32,0	16,0	0,85	30
14289RA01	38,1	19,0	0,96	30
14290RA01	50,8	25,4	0,97	30
14291RA01	76,2	38,1	1,30	30

**Notes:**

**Colour: Black**  
**Materials: Crosslinked Polyolefin**  
**Shrink ratio: 2:1**  
**Flame retardant**  
**Halogen free**  
**Flammability: UL224 VW-1**

**Operating temperature: -55 °C +125 °C**  
**Minimum shrink temperature +70 °C**  
**Minimum full recovery temperature: +100 °C**  
**Longitudinal change 0 ± 10% massimo**  
**All dimensions are in mm**  
**Available in other colors on special request**

				TITLE <b>THIN-WALL HEAT SHRINK TUBING 2:1</b>			
				MATERIAL SEE ABOVE		DATE 24/04/2020	
				COLOR SEE ABOVE		DRAWN R.F.	
PART NUMBER SEE TABLE		DRAWING NUMBER 20.04.24.142XX.0.E		CHECK			
SIZE A4	SCALE NTS	UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE			
				APPROVED			