

REVISIONS			
REV	DESCRIPTION	DATE	BY




P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Reel / Meter
14306RA09	1,6	0,5	0,50	150
14307RA09	2,4	0,8	0,51	150
14308RA09	3,0	1,0	0,53	150
14309RA09	4,8	1,5	0,6	75
14310RA09	6,4	2,0	0,65	75
14311RA09	9,5	3,0	0,75	75
14312RA09	12,7	4,0	0,75	50
14313RA09	19,1	6,0	0,80	30
14314RA09	25,4	8,0	1,0	30
14315RA09	39,0	13,0	1,15	30

Notes:

Colour: yellow-green
Material: Crosslinked Polyolefin
Shrink ratio: 3:1
Flame retardant
Flammability: UL224 VW-1
High flexibility

Operating temperature: -55 °C +135 °C
Minimum shrink temperature: +70 °C
Minimum full recovery temperature: +100 °C
Longitudinal change 0 ± 10% max.
All dimensions are in mm

				TITLE THIN-WALL HEAT SHRINK TUBING 3:1	
				MATERIAL SEE ABOVE	
PART NUMBER SEE TABLE				DRAWING NUMBER 20.04.24.143XX.0.E	
				COLOR SEE ABOVE	
SIZE A4	SCALE NTS	UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
				APPROVED	