

REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Bars length mt
14404TL13	1,52	0,97	0,30	1,22
14405TL13	1,93	1,17	0,30	1,22
14406TL13	2,36	1,45	0,30	1,22
14407TL13	3,05	1,82	0,30	1,22
14408TL13	3,81	2,26	0,30	1,22
14409TL13	4,85	2,80	0,30	1,22
14410TL13	6,1	3,55	0,38	1,22
14411TL13	7,67	4,40	0,38	1,22
14412TL13	9,4	5,45	0,38	1,22
14413TL13	10,92	6,90	0,38	1,22
14414TL13	11,94	8,56	0,38	1,22

**Notes:**

**Colour: Clear**

**Material: PTFE (TEFLON)**

**Shrink ratio: 1,5:1**

**Superior chemical and mechanical performance**

**Very low friction coefficient**


**Excellent electrical properties**

**Operating temperature: -65 °C +260 °C**

**Minimum full recovery temperature: +350 °C**

**Longitudinal change 0 ± 10% max.**

**All dimensions are in mm**

				TITLE <b>SPECIAL HEAT SHRINK TUBING IN TEFLON</b>	
				MATERIAL SEE ABOVE	DATE 24/04/2020
PART NUMBER SEE TABLE				DRAWN R.F.	
				DRAWING NUMBER 20.04.24.14XXX.0.E	
SIZE A4				COLOR SEE ABOVE	
				CHECK	
SCALE NTS		UNIT mm.		REV A	
UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE				APPROVED	