



DIM.	TOL.
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY

BEFORE INSERTION



AFTER INSERTION



P/N	A	B	C	HOLE	THICKNESS
9786EA01	24,0	20,0	14,0	Ø 5,1	1,0 - 2,3
9787EA01	20,0	18,0	10,0	Ø 5,1	1,0 - 2,3
9810EA01	30,0	28,0	15,0	Ø 5,1	0,8 - 2,0

Notes:

Body material: TPE

Pin material: PA 6

Screw material: Acetalic


Flammability:

-TPE: HB (UL94)

- PA 6: V2 (UL94)

- Acetalic: HB (UL94)

Working temperature: -35°C ~ +90°C

				TITLE FEETS WITH SNAP RIVET AND SCREW PIN	
				MATERIAL SEE ABOVE	DATE 15/09/2021
PART NUMBER SEE TABLE				DRAWN R.F.	
				DRAWING NUMBER 21.09.15.XXXX.0.E	
SIZE A4				COLOR BLACK	
				CHECK	
SCALE NTS		UNIT mm.		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
REV A		APPROVED			