


P/N	A	B	C	D	E
12819CA01	12,0	6,0	7,0	9,0	3,0
12820CA01	12,0	5,5	7,0	9,0	3,0
2422CA01	14,0	7,0	6,5	9,0	3,5
2423CA01	14,0	8,0	6,5	9,0	3,5
4683CA01	15,0	6,0	11,0	9,5	1,0
4684CA01	15,0	6,0	12,0	9,5	2,0
4685CA01	15,0	6,0	13,0	9,5	3,0
2291CA01	14,0	8,0	8,5	10,0	2,5
0882CA01	14,0	3,0	8,0	10,0	2,0
4587CA01	14,0	3,0	9,0	10,0	3,0
4588CA01	14,0	3,0	10,0	10,0	4,0
0883CA01	14,0	4,0	8,0	10,0	2,0
4589CA01	14,0	4,0	9,0	10,0	3,0
4590CA01	14,0	4,0	10,0	10,0	4,0
0884CA01	14,0	5,0	8,0	10,0	2,0
4591CA01	14,0	5,0	9,0	10,0	3,0
4592CA01	14,0	5,0	10,0	10,0	4,0
0885CA01	14,0	6,0	8,0	10,0	2,0
4593CA01	14,0	6,0	9,0	10,0	3,0
4594CA01	14,0	6,0	10,0	10,0	4,0
0886CA01	14,0	7,0	8,0	10,0	2,0
4595CA01	14,0	7,0	9,0	10,0	3,0
4596CA01	14,0	7,0	10,0	10,0	4,0
0887CA01	14,0	8,0	8,0	10,0	2,0
4597CA01	14,0	8,0	9,0	10,0	3,0
4598CA01	14,0	8,0	10,0	10,0	4,0
0849CA01	14,5	8,0	6,0	10,0	1,5
0864CA01	16,0	7,0	7,0	10,0	1,5
2395CA01	15,0	2,0	6,0	10,0	1,5
2396CA01	15,0	3,0	6,0	10,0	1,5
2397CA01	15,0	4,0	6,0	10,0	1,5
2398CA01	15,0	5,0	6,0	10,0	1,5
2399CA01	15,0	6,0	6,0	10,0	1,5
2400CA01	15,0	7,0	6,0	10,0	1,5
2401CA01	15,0	7,2	6,3	10,0	1,5
0889CA01	15,0	4,0	7,5	11,0	1,5
0891CA01	15,0	5,0	7,5	11,0	1,5
0893CA01	15,0	6,0	7,5	11,0	1,5
0895CA01	15,0	7,0	7,5	11,0	1,5
2340CA01	15,0	8,0	7,5	11,0	1,5
2342CA01	15,0	9,0	7,5	11,0	1,5

The technical drawing consists of two views of a shaft-hub assembly. The top view is a front view showing a shaft (inner circle) and a hub (outer ring). The dimension **A** is indicated twice: once as the diameter of the shaft and once as the thickness of the hub. The bottom view is a side view showing the shaft and hub in cross-section. The dimension **C** is the height of the shaft, **D** is the length of the hub, **B** is the length of the shaft, and **E** is the height of the hub.

TITLE: SOFT PVC GROMMETS		 DWG UNIT: MM	
Modelled in RHINO 4.0	FILE:	DwN: 11/05/21	ChkD:
TOLLERANCES UNLESS NOTED	SHEET: 1 OF 1	DT: 21.05.11.XXXXXX.0.E	Part Number: SEE TABLE
SEE ABOVE	SCALE: NTS	