

REVISIONS			
REV	DESCRIPTION	DATE	BY

Material: PET

Flammability: UL 224 VW-1; UL94-V2

Operating temperature: -50°C~150° C / Intermittent 220°C

Tensile Strength: 100,000 PSI


Colour: black and grey

Halogen free

All dimensions are in mm



<i>P/N Black</i>	<i>P/N Grey</i>	<i>Nominal diameter</i>	<i>Minimal diameter</i>	<i>Maximal diameter</i>	<i>PKG. MT.</i>
18385PT01	18385PT11	3,0	1,0	5,0	200
18386PT01	18386PT11	4,0	2,0	7,0	200
18387PT01	18387PT11	5,0	3,0	8,0	100
18388PT01	18388PT11	6,0	3,0	9,0	200
18389PT01	18389PT11	8,0	5,0	12,0	100
18390PT01	18390PT11	10,0	7,0	15,0	100
18391PT01	18391PT11	12,0	6,0	20,0	100
18392PT01	18392PT11	15,0	8,0	23,0	100
18393PT01	18393PT11	20,0	12,0	30,0	100
18394PT01	18394PT11	25,0	18,0	34,0	50
18395PT01	18395PT11	30,0	20,0	40,0	50
18396PT01	18396PT11	40,0	25,0	60,0	50
18397PT01	18397PT11	50,0	45,0	75,0	25

				TITLE EXPANDABLE BRAIDED SLEEVING	
				MATERIAL SEE ABOVE	
PART NUMBER SEE TABLE				DRAWING NUMBER 23.06.14.1838.0.E	
				COLOR SEE ABOVE	
SIZE A4		SCALE NTS		UNIT mm.	
REV A		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		CHECK APPROVED	