



REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside Ø (min.)	After recovery: inside Ø (max.)	After recovery: wall thickness (min.)	Reel / Meter
14843RA01	4,0	1,0	1,00	150,0
14844RA01	8,0	2,0	1,00	75,0
14845RA01	12,0	3,0	1,35	50,0
14846RA01	16,0	4,0	1,65	30,0
14847RA01	24,0	6,0	2,10	30,0
14848RA01	32,0	8,0	2,35	30,0

Notes:

Colour: Black

Material: Crosslinked co-extruded adhesive lined Polyolefin

Shrink ratio: 4:1

Flammability: UL224 VW-1

Flame retardant

Excellent sealing and insulation properties

Minimum shrink temperature +70°C

Minimum full recovery temperature +110°C

Longitudinal change 0 +/-10% max.

Operating temperature: -55 °C +125 °C

UV resistant

Available in lengths of 1,22

				TITLE HEAT SHRINK TUBING 4:1 RESISTANT 125°	
				MATERIAL SEE ABOVE	
PART NUMBER SEE TABLE				DRAWING NUMBER 21.12.14.XXX.0.E	
				COLOR SEE ABOVE	
SIZE A4	SCALE NTS	UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
				CHECKED	
				APPROVED	