



REVISIONS			
REV	DESCRIPTION	DATE	BY

UV RESISTANT  
WORKING TEMPERATURE: -40°C....+105°C  
HALOGEN AND PHOSPHORUS FREE

P/N	A	B	MOUNTING HOLE Ø	MAX. THICKNESS
5770AR01	6,4	6,1	4,7	1,6
5771AR01	7,9	7,9	6,4	1,6
5772AR01	9,5	7,9	7,9	1,6
5773AR01	11,9	10,3	9,5	3,2
5774AR01	13,5	10,3	11,1	3,2
5775AR01	14,7	13,2	12,7	3,2
5994AR01	14,7	14,3	12,7	6,4
17623AR01	18,5	13,2	15,9	3,2
5777AR01	18,2	10,3	15,9	6,4
17624AR01	23,1	13,2	19,1	6,4
5779AR01	23,4	10,3	19,1	3,2
5781AR01	25,8	11,5	22,2	3,2
18489AR01	14,7	14,3	12,7	6,4
18490AR01	30,6	14,3	25,4	6,4
5782AR01	30,6	11,5	25,4	3,2
5783AR01	30,9	11,5	27,8 - 28,6	3,2
18491AR01	30,9	14,3	27,8 - 28,6	6,4
5785AR01	34,9	11,5	31,7	3,2
18492AR01	34,9	14,3	31,7	6,4
5786AR01	38,1	11,5	34,9	3,2
18493AR01	38,1	14,7	34,9	6,4
18494AR01	42,4	14,3	38,1	6,4
5787AR01	42,8	11,5	38,1	3,2
5788AR01	48,7	11,5	44,5	6,4
1849AR01	48,4	14,3	44,5	6,4
5789AR01	55,1	11,9	50,8	6,4
18496AR01	55,1	14,7	50,8	6,4



TITLE		<b>HOLE PLUGS</b>	
MATERIAL		PA6.6 V0 (UL94)	DATE 03/08/2023
COLOR		BLACK	DRAWN A.C.
PART NUMBER		CHECK	
SEE TABLE		DRAWING NUMBER 23.08.03.5770X.E	
SIZE A4	SCALE NTS	UNIT mm	REV B
UNLESS OTHERWISE SPECIFIED TOLERANCE		APPROVED	